

5MP Full Color HD Camera

AB5S40MZ



Key Features

- Full Color Bullet
- 1/2.8"SONY Starvis Back-illuminated CMOS Sensor
- 2.7-13.5 mm Motorized Lens
- Support Warm white (4000K) up to 40m
- 4 IN 1 (AHD / CVI / TVI / CVBS)
- IP67 outdoor



www.iid2secure.nl Extra Benefits, Less Price Finestrat,19, 03530 La Nucia, Alicante, Spain © IID Secure Tech S.L.U. 2019 Heemdtedestraat 16 Amsterdam, Netherlands Support@iid2secure.nl +31614762425 Data Subject to change without notice



Specification

Model NO.	AB5S40MZ	
Video Output Mode	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps;	
	CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps	
	TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps;	
Camera		
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	
TV System	PAL/NTSC	
Electronic Shutter	Auto	
Scanning System	Progressive Scan	
Lens		
Focus Length	2.7-13.5mm Motor Zoom	
Focus Control	Auto	
Lens Type	Auto	
Night Vision		
IR Cut Filter	YES	
Infrared LED	NO, Support Warm white (4000K)	
Light Distance	up to 40m	
IR Status	AGC auto control	
Camera Features		
Starlight	YES	
Day/Night	YES/NO	
OSD Menu	YES	
WDR	YES	
UTC	YES	
Noise Reduction	3DNR	
Coaxial Audio	1	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	
General		
Housing	Metal, IP67	
Bracket	YES	
Operation Temperature	-10℃ ~ +60℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 750mA	
Dimension	268(W) x 95(H) x 88(D)mm	



www.iid2secure.nl
Extra Benefits, Less Price
Finestrat,19, 03530 La Nucia, Alicante, Spain
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands Support@iid2secure.nl +31614762425 Data Subject to change without notice



Material	Aluminum & SECC & PC
Dimension(WxHxD)	95 x 88 x 268 mm
Weight	1.50kg
Color	White
Operating Temperature	-20°C ~ +60°C
Humidity	< 95% RH

Dimensions





