



# 2MP Full Color HD Camera

AB5S60MZ



## Key Features

- Full Color Bullet
- 1/2.8" SONY Starvis Back-illuminated CMOS Sensor
- 2.7-13.5 mm Motorized Lens
- Support Warm white (4000K) up to 60m
- 4 IN 1 (AHD / CVI / TVI / CVBS)
- IP67 outdoor



[www.iid2secure.nl](http://www.iid2secure.nl)  
Extra Benefits, Less Price  
Finestrat, 19, 03530 La Nucia, Alicante, Spain  
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
[Support@iid2secure.nl](mailto:Support@iid2secure.nl)  
+31614762425  
Data Subject to change without notice



## Specification

|                              |  |
|------------------------------|--|
| <b>Model NO.</b>             | <b>AB5S60MZ</b>  |
| <b>Video Output Mode</b>     | AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps;<br>CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps<br>TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; |
| <b>Camera</b>                |  |
| <b>Image Sensor</b>          | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor   |
| <b>Image Resolution</b>      | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080  |
| <b>TV System</b>             | PAL/NTSC   |
| <b>Electronic Shutter</b>    | Auto   |
| <b>Scanning System</b>       | Progressive Scan   |
| <b>Lens</b>                  |  |
| <b>Focus Length</b>          | 2.7-13.5mm Motor Zoom  |
| <b>Focus Control</b>         | Auto   |
| <b>Lens Type</b>             | Auto   |
| <b>Night Vision</b>          |  |
| <b>IR Cut Filter</b>         | YES  |
| <b>Infrared LED</b>          | NO, Support Warm white (4000K)   |
| <b>Light Distance</b>        | up to 60m  |
| <b>IR Status</b>             | AGC auto control   |
| <b>Camera Features</b>       |  |
| <b>Starlight</b>             | YES  |
| <b>Day/Night</b>             | YES/NO   |
| <b>OSD Menu</b>              | YES  |
| <b>WDR</b>                   | YES  |
| <b>UTC</b>                   | YES  |
| <b>Noise Reduction</b>       | 3DNR   |
| <b>Coaxial Audio</b>         | /  |
| <b>White Balance</b>         | AUTO / MANUAL  |
| <b>Gain Control</b>          | AUTO   |
| <b>General</b>               |  |
| <b>Housing</b>               | Metal, IP67  |
| <b>Bracket</b>               | YES  |
| <b>Operation Temperature</b> | -10°C ~ +60°C RH95% Max  |
| <b>Storage Temperature</b>   | -20°C ~ +60°C RH95% Max  |
| <b>Power Source</b>          | DC12V±10%, 1000mA  |
| <b>Dimension</b>             | 220(W) x 109(H) x 106(D)mm   |
| <b>Weight</b>                | 2.15Kg   |



www.iid2secure.nl  
Extra Benefits, Less Price  
Finestrat,19, 03530 La Nucia, Alicante, Spain  
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
Support@iid2secure.nl  
+31614762425  
Data Subject to change without notice

|                       |                      |
|-----------------------|----------------------|
| Material              | Aluminum & SECC & PC |
| Dimension(WxHxD)      | 109 x 106x 220mm     |
| Weight                | 2.15kg               |
| Color                 | White                |
| Operating Temperature | -20°C ~ +60°C        |
| Humidity              | < 95% RH             |

## Dimensions

