



## 5MP Outdoor Full Color Fixed Dome Network camera



### SPECIFICATION

<b>Model NO.</b>	<b>DD5S25MN</b>
<b>Camera</b>	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Resolution	5MP
Effective Pixels	2616 (H)*1964 (V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
Audio Compression	G711A/U,AAC
TV System	PAL/NTSC
Electronic Shutter Time	Auto: 1/3-1/100000Sec
Minimum Illumination	Color: 0.001 Lux @ (F1.0, AGC ON), 0 Lux with white light
S/N Ratio	60dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional



[www.iid2secure.nl](http://www.iid2secure.nl)  
Extra Benefits, Less Price  
Finestrat,19, 03530 La Nucia, Alicante, Spain  
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
[Support@iid2secure.nl](mailto:Support@iid2secure.nl)  
+31614762425  
Data Subject to change without notice



<b>Lens</b>	
Focal Length & FOV	2.8 mm, horizontal FOV 111°, vertical FOV 60°, diagonal FOV 134° 3.6 mm, horizontal FOV 93°, vertical FOV 49°, diagonal FOV 110° 6 mm, horizontal FOV 57°, vertical FOV 30°, diagonal FOV 66°
Lens Type	Fixed focal lens, 2.8mm
Focus Control	Fixed
Aperture	F1.0
Pixels	5MP
<b>Night Vision</b>	
Infrared LED	No, Support Warm light LED 4000K, up to 25m
Infrared Distance	N/A
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP, IPv4/v6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP, SNMP, Qos, 802.1x
ONVIF	Support ONVIF 19.12(Profile S/T/G)
P2P	YES
POE	Internal, Support IEEE 802.3af
Video Delay	0.3S (Within the Lan)
Main Stream 1	2592*1944@30fp
Main Stream 2	2560*1440@30fp
Main Stream 3	1920*1080@30fps 1280*720@30fps
Sub Stream 1	1280*720@30fps
Sub Stream 2	720*480@30fps
Sub Stream 3	352*288@30fps
Tri Stream	1280*720@30fps 720*480@30fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Mac Safari
Smart Phone	iPhone, Android



[www.iid2secure.nl](http://www.iid2secure.nl)  
 Extra Benefits, Less Price  
 Finestrat, 19, 03530 La Nucia, Alicante, Spain  
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
[Support@iid2secure.nl](mailto:Support@iid2secure.nl)  
 +31614762425  
 Data Subject to change without notice



<b>AI Function</b>	
Intelligent Analysis	Face Detection, Intrusion Detection(with Vehicle Detection), Line Cross Detection(with Vehicle Detection), Loiter Detection, People Gather Detection(based on human detection),Motion detection based on human detection
<b>Camera Features</b>	
Day/Night	Color
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering, HLC, Distortion
Full Color	Support
Corridor Pattern	Support
Defog Mode	Support
ROI	Support
BLC	Support
WDR	120dB
Motion Detection	Support(support enable the detection based on human movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederland, Czech, Vietnamese
<b>Interface</b>	
Audio	Built-in MIC
Alarm	N/A
SD Card Slot	Optional Internal, Support Max 1TB
RS485	N/A
<b>General</b>	
Housing	Metal ,IP67
Anti-cut Bracket	No
IR Cut Filter	YES
Operation Temperature	-20°C~ +60°CRH95% Max
Storage Temperature	-20°C~ +60°CRH95% Max
Power Source	DC12V±10%, 1000mA
Dimension	∅ 96 x 91(H) mm
Weight	600g