



## IID-AD2I25F28M

1080P Four in One Analog Video Camera

### Key features:

- 1080P FHD resolution, the image is more clear and delicate
- Zero-latency data transmission, full real-time, high fidelity
- Long transmission distance, coaxial transmission up to 500 meters;
- Support UTC, enable OSD by the back-end;
- Support coaxial upgrade, version upgrade convenient and efficient;
- Support XVI/AHD/TVI/CVI DVR;
- NTSC&PAL 2 in 1, easy to switch through back-end;
- High-definition quality products with competitive price.



Specifications	IID-AD2I25F28M
ISP	XM330
Sensor	1/2.7 inch SC2235 sensor
Signal format	XVI/TVI/CVI
Video Resolution	PAL/NTSC : 1920*1080
Minimum Illumination	color: 0.01Lux@ (F1.2, AGC ON) , 0Lux with IR
	Black & White: 0.001Lux@ (F1.2, AGC ON) , 0Lux with IR
Noise Reduction	2D
OSD Menu	UTC Control
Shutter	1/50(1/60) seconds to 1/10,000 seconds
Day and Night Function	Support IR-CUT,25m IR distance
Lens Parameters	2.8mm
Video output	1080P@25fps
Power	DC12V±10%
Temperature and Humidity	- 10 °C ~ 60 °C , humidity is less than 90% (no condensation)
Consumption	<5W
Waterproof	IP66
Material	Metal



www.iid2secure.nl  
 Extra Benefits, Less Price  
 Finestrat,19, 03530 La Nucia, Alicante, Spain  
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
 Support@iid2secure.nl  
 +31614762425  
 Data Subject to change without notice