
## IID-AD2I40M





## **Key Features:**

- 1080P FHD resolution, the image is more clear and delicate
- Zero-latency data transmission, full real-time, high fidelity
- Long transmission distance, coaxial transmission up to 500 meters
- Support UTC, enable OSD by the back-end
- · Support coaxial upgrade, version upgrade convenient and efficient
- Support XVI/AHD/TVI/CVI DVR
- NTSC&PAL 2 in 1, easy to switch through back-end
- High-definition quality products with competitive price











<b>Specifications</b>	IID-AD2I40M
Image Sensor	1/2.7" 2MP CMOS
Min. Illumination	0.01Lux @F1.2 (Color)
	0.001 Lux @ F1.2 (B&W)
Frame Rate	50Hz:1080P@25fps
	60Hz:1080P@30fps
Lens	2.8-12mm
Day/Night	IR-CUT
Max.IR Distance	40m
IR LED	36pcs IR led
OSD Menu	UTC Control
Wide Dynamic Rang	DWDR
Noise Reduction	2D
Video Output	XVI/AHD/TVI/CVI
Audio In	-
Alarm In/Out	-
Ingression Protection	IP66
Working Temperature	-20°∼65°
Material	Metal
Power	DC12V±10%



www.iid2secure.nl Extra Benefits, Less Price Finestrat,19, 03530 La Nucia, Alicante, Spain © IID Secure Tech S.L.U. 2019 Heemdtedestraat 16 Amsterdam, Netherlands Support@iid2secure.nl +31614762425 Data Subject to change without notice