



IID-DB2I35F40MANWV

2.0M Black light illumination H.265 IP Camera

Features:

- 1080P HD resolution, clear and fine images;
- Support 2D/3D noise reduction, digital wide dynamic;
- Advanced H.265A1/H.265+ (Compatible with H.265/H.264) video compression, Super low rate, high definition quality of image;
- Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5.
- Support ONVIF; access third party;
- Support various mobile monitoring (iPhone, Android);
- Provide web、CMS、 center platform management software.
- Support cloud technology, easy to achieve network penetration, from in-line and alarm information pushed



| Model | IID-DB2I35F40MANWV |
|-----------------------|---|
| System structure | Embedded RTOS,dual-core 32bit DSP(XM530A1),pure hard compression ,watch dog |
| Sensor | 2.0M 1/2.9" IMX307 Black light illumination CMOS sensor,color 0.0001Lux@F1.2,black/white 0.0001Lux@F1.2 |
| Video compression | H.265A1/H.265+ (Compatible with H.265/H.264),support dual stream,AVI;0.1M~8Mbps variable;1~30f/s variable |
| Image output | Main stream: 1920*1080@25fps,1280*720@25fps; sub-stream: 704*576@25fps; |
| Shutter | 1/50(1/60)s to 1/10,000s |
| Lens | 4mm |
| Day and night | Support IR-CUT,35m IR Distance |
| Noise reduction | Support 2D/3D |
| Wide dynamic | Support digital |
| Auto iris | support |
| Audio compression | G.711,support bidirectional talk,audio&video synchronization |
| Audio interface | 1ch input,level:2Vp-p,impedance:1kΩ,support sound pick-up input;1ch output,impedance:16Ω,30mw,support microphone |
| Network interface | 1*RJ45 10/100M adaptive Ethernet port;support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc. |
| POE | Support |
| SD Card | N/A |
| Reliability | Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing |
| Intelligence analysis | Supporting human detection and tripping line detection |
| Other function | Support WEB, OSD, live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture united remote client monitoring software、MYEYE;perfect SDK; |
| ONVIF | Support |
| Mobile monitoring | Support multiple mobile monitoring (iOS, Android) |
| Power | DC12V/2A input, power consumption:≤3W, |
| Ingression Protection | Outdoor IP66 |
| Material | Metal |



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice