



IID-DB5I35F40MANV

5.0M H.265 Black light illumination IP Camera

Features:

- Supporting human detection and tripping line detection
- 5MP HD Black light illumination resolution, clear and fine images;
- Support 2D/3D noise reduction, digital wide dynamic;
- Advanced H.265A/H.265+ (Compatible with H.265/H.264) video compression, Super low rate, high definition quality of image;
- Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5.
- Support ONVIF; access third party Support various mobile monitoring (iPhone, Android);
- Provide web、CMS、center platform management software
- Support cloud technology, easy to achieve network penetration, from in-line and alarm information pushed



Model	IID-DB5I35F40MANV
System structure	Embedded RTOS,dual-core 32bit DSP(XM530AI),pure hard compression ,watch dog
Sensor	5.0M 1/2.8" IMX335 Black light illumination CMOS sensor, color 0.0001Lux@F1.2,black/white 0.0001Lux@F1.2
Video compression	H.265A/H.265+ (Compatible with H.265/H.264),support dual stream,AVI;0.1M~8Mbps variable;1~30f/s variable
Image output	Main stream: 5MP 2592*1944@15fps;4MP 2560*1440@20fps; 2MP 1920*1080@20fps; sub-stream: 704*576@25fps;
Shutter	1/50(1/60)s to 1/10,000s
Lens	4mm
Day and night	Support IR-CUT,35m IR Distance
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Auto iris	support
Audio compression	G.711,support bidirectional talk,audio&video synchronization
Audio interface	1ch input,level:2Vp-p,impedance:1kΩ,support sound pick-up input;1ch output,impedance:16Ω,30mw,support microphone
Network interface	1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc.
POE	Support
SD Card	N/A
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Intelligence analysis	Supporting human detection and tripping line detection
Other function	Support WEB, OSD, live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture; united remote client monitoring software、MYEYE;perfect SDK;
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring (iOS, Android)
Power	DC12V/2A input, power consumption:≤3W,
Ingression Protection	Outdoor IP66
Material	Metal



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice