



## IID-DB5I50MN

5.0M H.265 Intelligent analysis Network Camera

### Key Features:

- 5.0M HD resolution, clear and fine images
- Support multiple intelligent analysis
- Support 2D/3D noise reduction, digital wide dynamic
- Advanced H.265/H.264 video compression,
- Super low rate, high definition quality of image;
- Professional anti-lightning, conform to GB/T17626.5 and IEC61000-4-5
- Support ONVIF, access third party
- Support various mobile monitoring (iPhone, Android);
- Provide web CMS center platform management software
- Support cloud technology, easy to achieve network penetration, from in-line and alarm information pushed



| Model                 | IID-DB5I50MN   |
|-----------------------|--|
| System structure      | Embedded RTOS dual-core 32bit DSP(Hi3516D),pure hard compression ,watch dog  |
| Sensor                | 5.0M 1/2.5" PS5510 CMOS sensor ,color 0.1Lux@F1.2,black/white 0.01Lux@F1.2   |
| Video compression     | H.265/H.264,support dual stream,AVI;0.1M~10Mbps variable;1~30f/s variable  |
| Image output          | Main stream: 5MP 2592*1944@15fps;4MP 2560*1440@25fps;3MP 2048*1536@25fps; sub-stream: 704*576@25fps;   |
| Shutter               | 1/50(1/60)s to 1/10,000s   |
| Lens                  | 2.8-12mm lens  |
| IR Distance           | 50m  |
| IR LED                | 42pcs led  |
| Day and night         | Support IR-CUT   |
| Noise reduction       | Support 2D/3D  |
| Wide dynamic          | True, not less than 120dB  |
| ONVIF                 | Support  |
| Mobile monitoring     | Support multiple mobile monitoring (iOS Android)   |
| Intelligence analysis | Alarm line, alarm region, goods stranded, video block, fuzzy detection, scene change   |
| Network interface     | 1*RJ45 10/100M adaptive Ethernet port; support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc   |
| Reliability           | Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing  |
| Other function        | Support WEB OSD live video transmission, motion detect and IO alarm, front-end storage/playback/download, and center reminder and image linkage, support JPEG capture united remote client monitoring software, MYEYE perfect SDK; |
| Power                 | DC12V/2A input, power consumption:≤3W  |
| Ingression Protection | IP66   |
| material              | Metal  |
| Working Temperature   | -20°~65°   |



[www.iid2secure.nl](http://www.iid2secure.nl)

Extra Benefits, Less Price

Finestrat,19, 03530 La Nucia, Alicante, Spain

© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands

Support@iid2secure.nl

+31614762425

Data Subject to change without notice