



## Model: IID-DD5I25F28PAS



### Features:

1. ultra-high resolution, 2592 \* 1944, the image details are clearer;
2. Intelligent infrared / intelligent warm light technology, embedded AE deep intelligent learning algorithm, the face is clear without overexposure;
3. Support Extra-ISP night vision low smear image algorithm;
4. Support 3 kinds of image scene modes: transparent, bright, standard, image style switching as you like;
5. "Dark area perception algorithm" at night, the visibility of dark objects in the image is increased by 50%, but it does not affect the bright area exposure;
6. "Balanced Exposure Engine" at night. When people and cars approach, balance the exposure of the near and far images, the exposure of the near face is suppressed better, and the visible distance of distant scenes is about 5 meters longer than that of friends;
7. Support manual shutter, exposure adjustment, can see the contents of electronic screen, LED screen and instrument of each refresh frequency;
8. Support horizontal flip and vertical flip of images;

Model	IID-DD5I25F28PAS
System structure	Flash 16MB, DDR2 128MB
Sensor	5.0M 1/2.8" Hi3516EV300 Black light illumination CMOS sensor,color 0.0001Lux@F1.2,black/white 0.0001Lux@F1.2
Video compression	H.264、H.265
Image output	2592*1944@20 ( default ) 、 2592*1520@20 、 2560*1440@20 、 2304*1296@30 、 2304*1296@25 、 1080P@30、 1080p@25
Shutter	1/50(1/60)s to 1/10,000s
Lens	2.8mm/4mm
Day and night	25m IR Distance
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Auto iris	support
Audio compression	G.711,support bidirectional talk,audio&video synchronization



www.iid2secure.nl  
Extra Benefits, Less Price  
Finestrat,19, 03530 La Nucia, Alicante, Spain  
© IID Secure Tech S.L.U. 2019

Heemtedestraat 16 Amsterdam, Netherlands  
Support@iid2secure.nl  
+31614762425  
Data Subject to change without notice



Audio interface	1ch input,level:2Vp-p,impedance:1kΩ,support sound pick-up input;1ch output,impedance:16Ω,30mw,support
Network interface	1*RJ45 10/100M adaptive Ethernet port;support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP etc
POE	Support
SD Card	Support
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Intelligence analysis	No
Other function	Support WEB,OSD,live video transmission,motion detect and IO alarm,front-end storage/playback/download, and center reminder and image linkage,support JPEG capture
ONVIF	Support
Mobile monitoring	Support multiple mobile monitoring (iOS,Android)
Power	DC12V/2A input, power consumption:≤3W,
Ingression Protection	Indoor
Material	Plastic
Working environment	-30°C~60°C (-22°F~140°F)



[www.iid2secure.nl](http://www.iid2secure.nl)  
Extra Benefits, Less Price  
Finestrat,19, 03530 La Nucia, Alicante, Spain  
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands  
Support@iid2secure.nl  
+31614762425  
Data Subject to change without notice