



IID-DZ5I15036XMMASTW

Key Features:

- *7 Total Metal body construction, IP66 rate protection, Support with wiper
- *1/2.9" CMOS, 2.0 /4.0/5.0 Megapixels, 20X /36X optical zoom
- *HD-IP digital interface output, Support H.265/ H.264/MJPEG compression, triple stream, video output
- *OSD menu available
- *PWM function, intelligent IR illumination & power consumption is variable, depends the zoom factor
- *Strong compatibility, support standard ONVIF
- *seamless docking Hikvision, UOB, XM(CMS), Sky Vision UC2, The United States as the AEVISION, Milestone and other platforms
- *Laser + array combination, 8 PCS LED + 4 PCS laser, IR distance 180M



Camera	
module NO	IID-DZ5I15036XMMASTW
Sensor	5MP 3516A+SONY335 30FPS
Optical Zoom	36X 4.6-167MM
	F1.6~F2.7
View of Angle	D : WIDE 68.5°±5% TELE 4.2°±5% H : WIDE 54.8°±5% TELE 3.4°±5% V : WIDE 41°±5% TELE 2.5°±5%
	2592x1944、2592x1520、2304x1296、1920x1080、1280x960、1280x720、720x576、640x480
Min. Illumination	0.5 lx (F1.6, 50 IRE, ICR off), 0.095 lx (F1.6, 50 IRE, ICR on)/0.01Lux、 0.001Lux
AGC Control	Manual/Auto
S/N Rate	≥ 50db
White Balance	Manual/Auto
Camera module control interface	SONY VISCA(Signal level 3.3V), baud rate: 9.6 Kb/s, 19.2 Kb/s, 38.4 Kb/s stop bit: 1
	HITACHI COMMAND (Signal level 3.3V), baud rate: 4.8Kb/s, 9.6 Kb/s, 19.2 Kb/s, 38.4 Kb/s, 57.6Kb/s stop bit: 1
IR-cut	Manual/Auto



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucua, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice



Dome	
Communications Protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP
Storage (optional)	One SD/SDHC card
Software Control	IE, CMS, Management Platform
Mobile View(optional)	Support Windows, Symbian, iPhone platform smartphone
Horizontal Rotation Speed	60°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	45°/s
Tilt Rotation Range	90°
Auto Flip	Horizontal 180°, Vertical 180°
Auto Control IR LED	PWM
A-B Scan	User programmable
A-B Scan Speed	0-64 levels setting available
Dwell Preset	2-60s interval available
Preset Points	220
Go to Preset Speed	01-64 levels available
Guard Tours	4 groups
Guard Points	Max.16 points, dwell time user selectable
PWR On Action	Memory/Pattern 1/Tour 1/360° scan/A-B scan/Preset 1-8/None
Park Time	0-60mins available
3D Location	Support (DH-SD1)
Time Scheduling Function	8 tasks
Privacy Mask	Support
Auto Control IR LED	PWM
IR Illumination Distance	150m
IR LED	8 PCS LED + 4 PCS laser
Communication	RS485
Baud Rate	1200/2400/4800/9600bps
Operating Temperature	-40°- +60°
Operating Humidity	≤95% Non-Condensing
Heater & Blower	Auto temperature control
Power Supply	AC/DC15-28V ≤2A
Power Consumption	≤ 20W
Lightning Protection	Transient voltage 6000V
Package Size (CM)	31*31*44
Weight (KG)	5.5KG
2Pcs 1Box, Box size	65*34*47
2Pcs 1Box, Box Weight	11KG



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice