



# Network Keyboard

IID-KB1122



## Key Features

- 7" TFT touch screen at 800×480 resolution
- Speed dome, video decoder & DVR control
- 1-ch HD video stream decoding at 1080p
- Support 15 users, and each can operate up to 256 devices
- USB 2.0 interface for video backup

Specifications	IID-KB1122
<b>Audio Input/output</b>	
Line in	1-ch, 3.5 mm connector (2.0 Vp-p, 1 kΩ)
Audio out	1-ch, 3.5 mm connector (Linear, 560 Ω)
<b>External Interface</b>	
Network interface	1 RJ45 10M/100M/1000M self-adaptive Ethernet interface
RS-232 interface	1 RS-232 interface (for parameters configuration and maintenance)
RS-485 interface	1 RS-485 interface
USB interface	1, USB2.0 (for data storage and device upgrade)
<b>General</b>	
LCD	Resolution: 800 × 480
Power supply	12 VDC
Power consumption	≤ 15W
Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working humidity	10% ~ 90%
Dimensions (W × D × H)	110 × 193 × 435 mm
Weight	2 kg



www.iid2secure.nl  
Extra Benefits, Less Price  
Finestrat,19, 03530 La Nucia, Alicante, Spain  
© IID Secure Tech S.L.U. 2019

Heemstedestraat 16 Amsterdam, Netherlands  
Support@iid2secure.nl  
+31614762425  
Data Subject to change without notice