



IID-TS900 Tripod Turnstile

TECHNICAL DATA

Size: 1400*280*1000mm
 Housing material: SS304
 Pass Speed: 35 persons/min
 Working temperature: -35°C-55°C
 Gross weight: 65KG/PCS
 Passage width: 310mm
 Power supply: 110-220V 50/60Hz
 Motor voltage: Dc24v
 Working environment: Best for indoor
 Working humidity: ≤95% coagulation free
 Open while power off: Yes
 Working movement: DC24V Motor
 LED light: direction arrow
 Normal running life: 3 million



Tripod turnstile function & Features	Manual	Semi-Auto	Full-Auto
Alarm function: when arms are pushed by force illegally, alarm will be Triggered automatically and arms will be set locked	No	No	yes
Turnstile can setting the working condition by press the button of main board	No	Yes	Yes
Auto-lift-arm function: the arm can lift automatically with alert when the is on again	No action	Manual-lift-arm	Auto-lift-arm
Auto-drop-arm function: the arm can drop down automatically (default) (or free passing) when the power is off	No action	Auto-drop-arm	Auto-drop-arm
Automatic Reset Functions: after you swap the card, during the specific time (The system is 10s), if you didn't pass the turnstile, the system will cancel your Authority automatically to pass the gate, (reset time is 1~60s you can adjust it What time is suit for you)	No	Yes	Yes
The turnstile can work with door access control system/ consumption system biometric recognition system/ ESD system and so on	No	Yes	Yes
The turnstile is bidirectional (pedestrian can enter and exit from one set of turnstile)	No	Yes	Yes
LED indicator light	No	Yes	Yes
When pedestrian pass the turnstile, what should they do?	Manual push the arm	Manual push the arm	Automatic rotation
Once an open signal is given, the arms will rotate automatically to a 60 degree, and prompt the pedestrian to pass the gate	No	Yes	Yes
Can manager the turnstile directly by managing the computer	No	Yes	Yes
LED counting function	No	Yes	Yes



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice