IID-WT200

Sliding Turnstile

❖ Size: 1200*300*1000mm
❖ Housing material: SS304
❖ Pass Speed: 35 persons/min
❖ Working Temperature: -35 – 55 C
❖ Gross Weight: 55Kg
❖ Passage Width: 550 – 900mm
❖ Power Supply: 110-220V 50/60 HZ
❖ Motor Voltage: DC24V
❖ Working Environment: Better for indoor
❖ Working Humidity: <95% coagulation free
❖ Open while power off: Yes
❖ Working Movement: CD24V Motor
❖ LED Light: Direction arrow
❖ Normal Running Life: 5 Million

Features:

▪ Alarm Function: When arms are pushed by force illegally, alarm will be triggered automatically and arms will be set locked, turnstile can check by itself when it is having problem. It is good for customer to maintain and use.
▪ Turnstile can setting the working condition by pressing the button of main control board.
▪ Anti-pinch function: Turnstile have mechanical / infrared induction Anti-pinch (when it meets the hinder during the reset time, the turnstile will default the delayed and reset again till reset succeeded).
▪ Before receiving the open signal, the turnstile will lock automatically.
▪ The arm has the collision avoidance function: when the turnstile arm closed, it it is under the collision, the arm will open to protect the transmission of inner machine.
▪ Automatic Reset Function: after swapping the card, during the specific time (the system is10 seconds), if you didn't pass the turnstile, the system will cancel your authority automatically to pass the gate,(reset time is 1 - 60seconds Time Adjustable.), totally meets the fire protection needs.
▪ Infrared Reset Function (Optional 4 pairs or 6 pairs Infrared)
▪ The turnstile is bidirectional.
▪ The turnstile can work with door access control system / consumption system / biometric recognition system / ESD system)
▪ Can manage and long-range control the turnstile directly by managing the computer.
▪ Flashing Light Prompt Function: It's convenient to find the turnstile problem by administrative staff.
▪ Barrier free mode.