



IID-XVR08UPS MODIFIED



Key Feature :

- Support VGA, HDMI full HD output simultaneously;
- Support ONVIF; access third party;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support web, CMS, center platform management software MYEYE, provide SDK development;
- Support various mobile monitoring (iPhone, Android);
- Remote Access, With DNS (ARSP),easy to monitor remotely
- Support UTC, control signal& video stream transmit through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP Six signals;

Model		IID-XVR08UPS
System	Main chip	Hi3520D
	OS	LINUX
	System Resources	Multi-channel Realtime recording, Multi-channel playback, Multi-channel network operation, USB Backup
Interface	Operation menu	16-bit true color graphical menu interface, mouse operation supported
	Display	1/4 display (take the pure coaxial input mode as an example)
Video	Format	H.264
	Output	VGA、HDMI
	Preview	4*1080P@25fps
	Recode	4*1080P@15fps
	Decord	4*1080P@15fps
	Multi-mode Input	AHD : 8*1080P Hybrid : 4*1080P (HD)+4*1080P (IP) NVR : 8*1080P + 8*960P ; 4*3M ; 4*5M
	Motion Detect	Each view window can set 192 (16*12) detection area,can set multi-level sensitivity (only for local channel)
Audio	Audio	G.711A
	Intercom	Support
Recording and Playback	Recording mode	Manual、Alarm、Motion Detect、Timer
	Local playback	4 Channel (when Analog mode)
	Video search	Time, Date,Event,Channel search
	UPS power	Support



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucua, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice



Storage and Backup	Storage	Local HDD, Network
	Backup	Network back, USB Drive, HDD
Port	Video Input	8 * BNC
	Video Output	1 * VGA, 1 * HDMI
	Spot Monitor	NA
	Audio Input	4 * RCA
	Audio Output	1 * RCA
	Alarm Input	NA
	Alarm Output	NA
	Network port	RJ45 10M/100M
	PTZ Control	1 * RS485 Support multipal PTZ Contract
	USB port	2 * USB Port
	HDD Port	1* SATA hdd ports (up to 6T for each one)
Wireless Port	3G、WIFI(can be USB WIFI Dongle)	
Others	Power	1*HDD: 12V/2A 2*HDD: 12V/5A
	Power consumption	Less than 15W (no HDD)
	Working temperature	0°C—+55°C
	Working humidity	10%—90%
	Atmospheric pressure	86kpa—106kpa



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice