

IID-XVR16P



Key Feature:

- Support VGA, HDMI full HD output simultaneously
- Support ONVIF; access third party
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions
- Support web, CMS, center platform management software MYEYE, provide SDK development
- Support various mobile monitoring (iPhone, Android)
- Remote Access, With DNS (ARSP), easy to monitor remotely
- Support UTC, control signal& video stream transmits through one single coaxial
- Support XVI/AHD/TVI/CVI/CVBS/IP Six signals

| | | |
|---------------|--|---|
| | Model | IID-XVR16P |
| System | Main chip | Hi3521A |
| | OS | LINUX |
| | System Resources | Multi-channel Realtime recording, Multi-channel playback, Multi-channel network operation, USB Backup |
| Interface | Operation menu | 16-bit true color graphical menu interface, mouse operation supported |
| | Display | 1/4/8/9/16 display (take the pure coaxial input mode as an example) |
| Video | Format | H.264 |
| | Output | VGA,HDMI;HD |
| | Preview | 16*1080P@25fps |
| | Recode | 16*1080P @12fps |
| | Decord | 16*1080P @12fps |
| | Multi-mode Input | Analog:16*1080P;8*1080P;16*1080N; Hybrid : 8*1080P (Analog) +8*10800P (IP) NVR : 8*1080P+8*960P; 8*3M ;4*5M |
| Motion detect | Each view window can set 192 (16*12) detection area,can set multi-level sensitivity (only for local channel) | |
| Audio | Audio | G.711A |
| | Intercom | Support |



www.iid2secure.nl
Extra Benefits, Less Price
Finestrat,19, 03530 La Nucia, Alicante, Spain
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
+31614762425
Data Subject to change without notice



| | | |
|------------------------|----------------------|---|
| Recording and Playback | Recording mode | Manual、Alarm、Motion Detect、Timer |
| | Local playback | 16 Channel (when Analog mode) |
| | Video search | Time, Date,Event,Channel search |
| Storage and Backup | Storage | Local HDD, Network |
| | Backup | Network back, USB Drive, HDD |
| Port | Video Input | 16 * BNC |
| | Video Output | 1 * VGA, 1 * HDMI |
| | Spot Monitor | NO |
| | Audio Input | 6 channel |
| | Audio Output | 1 * RCA |
| | Alarm Input | 4 channel |
| | Alarm Output | 1 channel |
| | Network port | RJ45 10M/100M |
| | PTZ Control | 1 * RS485 ; Support multupal PTZ Contract |
| | USB port | 2 * USB Port |
| | HDD Port | 2 * SATA port (Up to 6T for each one) |
| | Wireless | 3G、WIFI(can be USB WIFI Dongle) |
| Others | Power | 2*HDD: 12V/5A 4 * HDD: 12V/6A |
| | Power consumption | Less than 15W (no HDD) |
| | Working temperature | 0 —+55 |
| | Working humidity | 10%—90% |
| | Atmospheric pressure | 86kpa—106kpa |



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice