



IIDMDG-3000V3

High Sensitivity Digital Walkthrough Metal Detector



Product Introduction

IIDMDG-3000V3 high sensitivity digital walkthrough metal detector use excellent electromagnetic testing and digital processing technology, has high detection sensitivity of the magnetic metal and nonmagnetic metal, and good recognition for personal items such as coins, keys, belt buckle, etc. multi-layered overlapping coil design, with high-brightness LEDs to show the horizontal position of metal objects accurately, which can be easy for operator to make judgment.

Technology Features

- ◆ High detection sensitivity for the magnetic metal, non-magnetic metal and alloy.
- ◆ Self-diagnostic program, power-on self-test, modular structure, multi-language selection, the system automatically wake up.
- ◆ Highly integrated DSP digital processing technology, no need tools to adjust, performance is more stable, more convenient after-sales service
- ◆ 33 detecting area, each area can setsensitivity alone.
- ◆ Has 300 effective sensitivity
- ◆ High-brightness color LCD; display function of power-on diagnose.
- ◆ 30 preset detection program.
- ◆ 100 optional frequency
- ◆ Real-time monitor of background environment interference

Applications

- ◆ Prison
- ◆ Bus Station
- ◆ Bank



www.iid2secure.nl
Extra Benefits, Less Price
Finestrat,19, 03530 La Nucia, Alicante, Spain
© IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
+31614762425
Data Subject to change without notice



Technology Data

- Detection Sensitivity33 detecting area, with high-brightness LED alarm, Precise positioning the location of hiding contraband.
- Sensitivity Level300 level adjustable for each detecting area
- Frequency Setup 100 optional working frequency
- Audible Alarm 20 volume levels adjustable, 16 tones levels adjustable
- Display Screen Color LCD display, Chinese/ English language select menu,Real-time display interference signal
- Preset Working Model30 security check working models, all parameters of detecting procedures can be set or modified at any time.
- Operation Authorization Password protection allows only authorized personnel operate
- Throughput 100 people/min
- Counting FunctionEquipped with intelligent traffic and alarm counter,Real-time automatically displays the number of alarm and people, maximum100,000 records.
- Energy-saving Function The system will automatically enter power-saving mode when it is no detecting in 5 mins, and will wake up when there is object.
- Anti-interference Highly integrated DSP digital processing technology Automatically detects environmental interference; Resistance to electromagnetic and mechanical interference; non-periodically calibration; no alarm errors caused by vibration and shaking. Anti-interference Capability...50cm for devices adjacent side by side
- Diagnostic function Power-on self-test, fault Display,Allcontrol information and settings can be operated on control panel and menu
- Procedure Computer programming controller, Chinese and English optional language, modular structure
- Safety No harm to pacemaker wearers, Pregnant woman and magnetic media.
- Backup power supply: 4/8/10 hours battery power supply
- IP GradeP65

Installation Data

- Size/Weight2230mm (L)*820mm (W)*550mm (H)/65KG
- Tunnel Size.....2000mm (L)*710mm (W)*500mm (H)
- Power SupplyExternal power adapter, AC100-240V/50-60Hz
- Power Consumption <15W
- Working Temperature..... -20 °C~+50°C



Notice : Specifications are subject to change without notice.



www.iid2secure.nl
 Extra Benefits, Less Price
 Finestrat,19, 03530 La Nucia, Alicante, Spain
 © IID Secure Tech S.L.U. 2019

Heemdtedestraat 16 Amsterdam, Netherlands
 Support@iid2secure.nl
 +31614762425
 Data Subject to change without notice