



IIDMDG-3000V9

High Sensitivity Digital Walkthrough Metal Detector



Product Introduction

IIDMDG-3000V2 high sensitivity digital walkthrough metal detector use excellent electromagnetic testing and digital processing technology, has high detection sensitivity of the magnetic metal and nonmagnetic metal, and good recognition for personal items such as coins, keys, belt buckle, etc. multi-layered overlapping coil design, with high-brightness LEDs to show the horizontal position of metal objects accurately, which can be easy for operator to make judgment.

Technology Features

- ◆ High detection sensitivity for the magnetic metal, non-magnetic metal and alloy.
- ◆ Self-diagnostic program, power-on self-test, modular structure, multi-language selection, the system automatically wake up.
- ◆ Highly integrated DSP digital processing technology, no need tools to adjust, performance is more stable, more convenient after-sales service
- ◆ 24 detecting area, each area can set sensitivity alone.
- ◆ Has 300 effective sensitivity
- ◆ High-brightness color LCD; display function of power-on diagnose.
- ◆ 30 preset detection program.
- ◆ 100 optional frequency
- ◆ Real-time monitor of background environment interference

Applications

Prison
Airport

Bus Station
Factories

Bank
Venues



www.iid2secure.nl
Extra Benefits, Less Price
Finestrat,19, 03530 La Nucia, Alicante, Spain
© IID Secure Tech S.L.U. 2019

Heemdedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
+31614762425
Data Subject to change without notice



Technology Data

Detection Sensitivity.....	24 detecting area, with high-brightness LED alarm, Precise positioning the location of hiding contraband.
Sensitivity Level.....	300 level adjustable for each detecting area
Protection	Outdoor IP65
Frequency Setup	100 optional working frequency
Audible Alarm	20 volume levels adjustable, 16 tones levels adjustable
Display Screen.....	Color LCD display, Chinese/ English language select menu,Real-time display interference signal
Preset Working Model.....	30 security check working models, all parameters of detecting procedures can be set or modified at any time.
Operation Authorization	Password protection allows only authorized personnel operate
Throughput	100 people/min
Counting Function.....	Equipped with intelligent traffic and alarm counter,Real-time automatically displays the number of alarm and people, maximum 100,000 records.
Energy-saving Function	The system will automatically enter power-saving mode when it is no detecting in 5 mins, and will wake up when there is object.
Anti-interference	Highly integrated DSP digital processing technology Automatically detects environmental interference; Resistance to electromagnetic and mechanical interference; non-periodically calibration; no alarm errors caused by vibration and shaking. Anti-interference Capability...50cm for devices adjacent side by side
Diagnostic function.....	Power-on self-test, fault Display,All control information and settings can be operated on control panel and menu
Procedure	Computer programming controller, Chinese and English optional language, modular structure
Safety	No harm to pacemaker wearers, Pregnant woman and magnetic media.

Installation Data

Size/Weight	2200mm (L)*800mm (W)*550mm (H)/65KG
Tunnel Size.....	2000mm (L)*700mm (W)*500mm (H)
Power Supply.....	External power adapter, AC85-264V/47.5-60HZ
Power Consumption.....	<15W
Working Temperature	-20°C~+50°C

Notice : Specifications are subject to change without notice.



www.iid2secure.nl
Extra Benefits, Less Price
Finestrat, 19, 03530 La Nucia, Alicante, Spain
© IID Secure Tech S.L.U. 2019

Heemtedestraat 16 Amsterdam, Netherlands
Support@iid2secure.nl
+31614762425
Data Subject to change without notice